NSN 5945-01-222-3903

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-222-3903

Overall Length:

0.810 inches

Overall Height:

0.410 inches

Overall Width:

0.410 inches

Environmental Protection:

Hermetic and shock resistant and vibration resistant

Winding Quantity:

1

Coil Quantity:

1

Winding Dc Resistance Rating:

160.0 ohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

1 plug-in terminal single mounting facility

Features Provided:

Coil voltage suppression

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Criticality Code Justification:

Feat

Time Delay:

0.005 seconds fixed operate and release time

Operating Voltage Rating And Type At Specificationified Temp:

12.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

160.0 milliamperes dc lamp load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Special Features:

Failure rate level 0.1 percent

Test Data Document:

81349-mil-r-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

8 pin all functions

Specification Data:

81349-mil-r-39016/22 government specification

Shelf Life:

N/a

NSN 5945-01-222-3903

Electromagnetic Relay - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A03300

