NSN 5945-01-223-3055

Electromagnetic Relay - Page 1 of 2

Overall Length:



View Online at https://aerobasegroup.com/nsn/5945-01-223-3055

| 2.440 inches |
|---|
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.000 inches single mounting facility |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 2.000 inches single mounting facility |
| Overall Height: |
| 2.500 inches |
| Overall Width: |
| 2.440 inches |
| Case Material: |
| Plastic |
| Environmental Protection: |
| Hermetic |
| Unthreaded Mounting Hole Diameter: |
| 0.170 inches single mounting facility |
| Fragility Factor: |
| Moderately rugged |
| End Application: |
| Panel, control |
| Winding Quantity: |
| 1 |
| Purpose For Which Designed: |
| General |
| Coil Quantity: |
| 1 |
| Winding Dc Resistance Rating: |
| 200.0 ohms single winding |
| Duty Type: |
| Continuous |
| Arc Quenching Method: |
| Air |
| Mounting Facility Type And Quantity: |
| 4 unthreaded hole single mounting facility |
| Storage Type: |
| General purpose warehouse |
| Features Provided: |
| Polarized |
| Cubic Measure: |
| 14.884 cubic inches |
| Mounting Facility Pattern: |

Rectangular single mounting facility

NSN 5945-01-223-3055

Electromagnetic Relay - Page 2 of 2



Nonpile-up Main Contact Arrangement:

3 pole, single throw, normally open, momentary action

Time Delay:

0.05 seconds fixed operate time

Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

15.0 amperes ac lamp load and 10.0 amperes dc lamp load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Energizing Element Power Rating:

4.35 watts

Terminal Type And Quantity:

8 threaded stud all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300