NSN 5945-01-223-9344

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-223-9344

Overall Length:

1.180 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.125 inches single mounting facility

Overall Height:

1.020 inches

Overall Width:

0.400 inches

Case Material:

Metal

Environmental Protection:

Shock resistant and vibration resistant and dustproof

Unthreaded Mounting Hole Diameter:

0.096 inches single mounting facility

Fragility Factor:

Moderately rugged

End Application:

Vmisc

Winding Quantity:

1

Purpose For Which Designed:

General

Coil Quantity:

1

Winding Dc Resistance Rating:

540.0 ohms single winding and 660.0 ohms single winding

Duty Type:

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

2 unthreaded hole single mounting facility

Storage Type:

General purpose warehouse

Cubic Measure:

0.481 cubic inches

Mounting Facility Pattern:

Diagonal single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

NSN 5945-01-223-9344

Electromagnetic Relay - Page 2 of 2



Time Delay:

0.005 seconds fixed operate and release time **Operating Voltage Rating And Type At Specificationified Temp:** 26.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 2.0 amperes ac resistive load and 2.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc **Terminal Type And Quantity:** 8 wire hook all functions Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A03300