## NSN 5945-01-223-9345

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-223-9345

Thread Class:
2a single mounting facility
Thread Direction:
Right-hand single mounting facility
Overall Length:
1.230 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.875 inches single mounting facility
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.625 inches single mounting facility
Overall Height:
1.660 inches
Overall Width:
0.980 inches
Case Material:
Metal
Environmental Protection:
Dustproof
Fragility Factor:
Moderately rugged
End Application:
Test set exci
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
4 threaded stud single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
2.000 cubic inches
Thready Qty Per Inch (tpi):
40 single mounting facility
Thread Size:
0.112 inches single mounting facility

## NSN 5945-01-223-9345

Electromagnetic Relay - Page 2 of 2



**Mounting Facility Pattern:** Rectangular single mounting facility Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary **Time Delay:** 0.05 seconds adjustable operate time and 15.00 seconds adjustable operate time **Operating Voltage Rating And Type At Specificationified Temp:** 28.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 10.0 amperes ac resistive load and 2.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc **Thread Series Designator:** Unc single mounting facility **Terminal Type And Quantity:** 8 wire hook all functions Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A03300