NSN 5945-01-224-0112

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-224-0112

| Thread Class: |
|--|
| 2b single mounting facility |
| Thread Direction: |
| Right-hand single mounting facility |
| Thread Length: |
| 0.062 inches single mounting facility |
| Overall Length: |
| 1.920 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.427 inches single mounting facility and 1.447 inches single mounting facility |
| Overall Height: |
| 1.830 inches |
| Overall Width: |
| 1.320 inches |
| Case Material: |
| Plastic |
| Contact Material: |
| Silver |
| Contact Surface Treatment: |
| Gold flash and silver plated |
| End Application: |
| 6525-01-159-3009 field radiographic/fluoroscopic x-ray systems; model dxd 350 ii |
| Frequency In Hertz: |
| 60.0 |
| Purpose For Which Designed: |
| General |
| Coil Quantity: |
| 1 |
| Duty Type: |
| Continuous |
| Mounting Facility Type And Quantity: |
| 2 threaded hole single mounting facility |
| Pile-up Main Contact Form Arrangement: |
| 1a and 1b |
| Cubic Measure: |
| 4.638 cubic inches |
| Thread Size: |
| 0.138 inches single mounting facility |
| Mounting Facility Pattern: |
| In-line single mounting facility |
| Minimum Differential Electrical Operating Rating |

160.0 milliamperes

NSN 5945-01-224-0112

Electromagnetic Relay - Page 2 of 2



Main Contact Load Current Rating At Maximum Rated Voltage:

710.0 milliamperes ac resistive load

Main Contact Maximum Voltage Rating In Volts:

150.0 ac

Precious Material And Location:

Contact gold and internal contact surfaces silver

Precious Material:

Gold and silver

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

4 banana plug all functions

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A03300