NSN 5945-01-224-6532

Electromagnetic Relay - Page 1 of 2

0.750 inches single mounting facility

Overall Length: 2.187 inches

Overall Height: 2.684 inches Overall Width: 1.531 inches



View Online at https://aerobasegroup.com/nsn/5945-01-224-6532

Center To Center Distance Between Mounting Facilities Parallel To Width:

Case Material:
Metal
Environmental Protection:
Hermetic
Unthreaded Mounting Hole Diameter:
0.147 inches single mounting facility
Fragility Factor:
Moderately rugged
End Application:
F-18-dcn t d
Winding Quantity:
2
Purpose For Which Designed:
General
Coil Quantity:
2
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
3 unthreaded hole single mounting facility
Storage Type:
General purpose warehouse
Features Provided:
Latching contacts
Cubic Measure:
8.987 cubic inches
Mounting Facility Pattern:
Triangle single mounting facility
Nonpile-up Main Contact Arrangement:
2 pole, double throw, one position momentary
Operating Current Rating And Type:
75.0 milliamperes ac all windings

NSN 5945-01-224-6532

Electromagnetic Relay - Page 2 of 2



Time Delay:

0.05 seconds fixed operate and release time

Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:

1.844 inches single mounting facility

Operating Voltage Rating And Type At Specificationified Temp:

120.0 volts ac 25 degrees celsius all windings

Main Contact Load Current Rating At Maximum Rated Voltage:

10.0 amperes ac resistive load and 10.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Terminal Type And Quantity:

10 pin all functions

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A03300