## NSN 5945-01-224-6573

Electrical Solenoid - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-224-6573

Body Style:
O-frame
Center To Center Distance Between Mounting Facilities Parallel To Length:
2.000 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.375 inches
Mounting Slot Width:
0.208 inches
Body Length:
2.500 inches
Body Width:
1.822 inches
Body Height:
2.094 inches
Fragility Factor:
Moderately rugged
Frequency In Hertz:
60.0
Inclosure Type:
Partially enclosed, shell
Magnetic Coil Quantity:
g,.
1
1
1 Duty Type:
1  Duty Type:  Continuous
1 Duty Type: Continuous Terminal Location:
1 Duty Type: Continuous Terminal Location: One side
Duty Type: Continuous Terminal Location: One side Voltage Rating In Volts:
Duty Type: Continuous Terminal Location: One side Voltage Rating In Volts: 120.0 ac
Duty Type: Continuous Terminal Location: One side Voltage Rating In Volts: 120.0 ac Mounting Facility Type And Quantity:
Duty Type: Continuous Terminal Location: One side Voltage Rating In Volts: 120.0 ac Mounting Facility Type And Quantity: 4 slot
Duty Type: Continuous Terminal Location: One side Voltage Rating In Volts: 120.0 ac Mounting Facility Type And Quantity: 4 slot Current Rating:
Duty Type: Continuous Terminal Location: One side Voltage Rating In Volts: 120.0 ac Mounting Facility Type And Quantity: 4 slot Current Rating: 410.0 milliamperes
Duty Type: Continuous Terminal Location: One side Voltage Rating In Volts: 120.0 ac Mounting Facility Type And Quantity: 4 slot Current Rating: 410.0 milliamperes Storage Type:
Duty Type: Continuous Terminal Location: One side Voltage Rating In Volts: 120.0 ac Mounting Facility Type And Quantity: 4 slot Current Rating: 410.0 milliamperes Storage Type: General purpose warehouse
Duty Type: Continuous Terminal Location: One side Voltage Rating In Volts: 120.0 ac Mounting Facility Type And Quantity: 4 slot Current Rating: 410.0 milliamperes Storage Type: General purpose warehouse Cubic Measure:
Duty Type: Continuous Terminal Location: One side Voltage Rating In Volts: 120.0 ac Mounting Facility Type And Quantity: 4 slot Current Rating: 410.0 milliamperes Storage Type: General purpose warehouse Cubic Measure: 9.538 cubic inches
Duty Type: Continuous Terminal Location: One side Voltage Rating In Volts: 120.0 ac Mounting Facility Type And Quantity: 4 slot Current Rating: 410.0 milliamperes Storage Type: General purpose warehouse Cubic Measure: 9.538 cubic inches Actuator Stroke Type:
Duty Type: Continuous Terminal Location: One side Voltage Rating In Volts: 120.0 ac Mounting Facility Type And Quantity: 4 slot Current Rating: 410.0 milliamperes Storage Type: General purpose warehouse Cubic Measure: 9.538 cubic inches Actuator Stroke Type: Pull

Plain-drilled

## NSN 5945-01-224-6573

Electrical Solenoid - Page 2 of 2



<b>Energizing Stroke Maximum Length:</b>
0.375 inches
Mounting Facility Pattern:
Four position rectangular
Unpackaged Unit Weight:
17.000 ounces
Terminal Type And Quantity:
2 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A134a0