NSN 5945-01-224-9044

Reed Relay - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5945-01-224-9044 |
|---------------------------------------------------------------------------------|
| Overall Length: |
| 2.750 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.200 inches single mounting facility |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 0.400 inches single mounting facility |
| Overall Height: |
| 0.980 inches |
| Overall Width: |
| 0.720 inches |
| Case Material: |
| Glass |
| Contact Material: |
| Nickel |
| End Application: |
| 6525-01-159-3009 field radiographic/fluoroscopic x-ray system; model dxd 350 ii |
| Purpose For Which Designed: |
| General |
| Coil Quantity: |
| 1 |
| Winding Dc Resistance Rating: |
| 320.0 ohms all windings |
| Duty Type: |
| Continuous |
| Mounting Facility Type And Quantity: |
| 4 printed circuit terminal single mounting facility |
| Cubic Measure: |
| 1.940 cubic inches |
| Operating Voltage Rating And Type At Specificationified Temp: |
| 12.0 volts dc 25 degrees celsius all windings |
| Main Contact Load Current Rating At Maximum Rated Voltage: |
| 1.0 amperes dc resistive load |
| Main Contact Maximum Voltage Rating In Volts: |
| 12.0 dc |
| Energizing Element Power Rating: |
| 450.0 milliwatts |
| Precious Material And Location: |
| Contact surfaces gold |
| Precious Material: |
| Gold |
| |

4 pin all functions

NSN 5945-01-224-9044

Reed Relay - Page 2 of 2



| _ | | | | | |
|---|---|------------|---|----|----|
| • | n | 0 1 | • | 12 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300