# NSN 5945-01-224-9610

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-224-9610

# Overall Length: 1.718 inches

# Center To Center Distance Between Mounting Facilities Parallel To Width:

0.625 inches single mounting facility

#### **Overall Height:**

1.310 inches

#### **Overall Width:**

1.010 inches

#### Mounting Slot Width:

0.150 inches single mounting facility

#### Case Material:

Metal

**Environmental Protection:** 

#### Hermetic

#### Fragility Factor:

#### Moderately rugged

End Application:

#### Vmisc

Winding Quantity:

1

**Purpose For Which Designed:** 

General

#### **Coil Quantity:**

1

## Duty Type:

Continuous

# Arc Quenching Method:

Air

# Mounting Facility Type And Quantity:

3 slotted hole single mounting facility

# Storage Type:

General purpose warehouse

## Features Provided:

Polarized

# Cubic Measure:

2.273 cubic inches

# Mounting Facility Pattern:

Triangle single mounting facility

# Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

# Operating Current Rating And Type:

150.0 milliamperes dc single winding

# NSN 5945-01-224-9610

Electromagnetic Relay - Page 2 of 2



#### **Time Delay:**

0.10 seconds adjustable operate time and 1.00 seconds adjustable operate time Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle: 1.396 inches single mounting facility and 1.446 inches single mounting facility **Operating Voltage Rating And Type At Specificationified Temp:** 30.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 2.0 amperes ac lamp load and 2.0 amperes dc lamp load Main Contact Maximum Voltage Rating In Volts: 200.0 ac and 28.0 dc **Terminal Type And Quantity:** 8 wire hook all functions Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A03300