NSN 5945-01-226-1917

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-226-1917

| Overall Length: |
|---|
| 1.531 inches |
| Overall Height: |
| 2.197 inches |
| Overall Width: |
| 1.406 inches |
| Case Material: |
| Plastic |
| Environmental Protection: |
| Dustproof |
| Fragility Factor: |
| Moderately rugged |
| Contact Material: |
| Silver |
| Contact Surface Treatment: |
| Gold flash |
| Winding Quantity: |
| 1 |
| Purpose For Which Designed: |
| General |
| Coil Quantity: |
| 1 |
| Winding Dc Resistance Rating: |
| 650.0 ohms single winding |
| Duty Type: |
| Continuous |
| Arc Quenching Method: |
| Air |
| Mounting Facility Type And Quantity: |
| 1 plug-in terminal single mounting facility |
| Storage Type: |
| General purpose warehouse |
| Cubic Measure: |
| 4.729 cubic inches |
| Nonpile-up Main Contact Arrangement: |
| 4 pole, double throw, one position momentary |
| Time Delay: |
| 0.013 seconds fixed operate time |
| Operating Voltage Rating And Type At Specificationified Temp: |
| 24.0 volts dc 25 degrees celsius single winding |
| Main Contact Load Current Rating At Maximum Rated Voltage: |

5.0 amperes ac resistive load and 5.0 amperes dc resistive load

NSN 5945-01-226-1917

Electromagnetic Relay - Page 2 of 2



Main Contact Maximum Voltage Rating In Volts:

120.0 ac and 28.0 dc

Precious Material And Location:

Contacts silver and contact surfaces gold

Precious Material:

Silver and gold

Terminal Type And Quantity:

14 tab, solder lug all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300