

View Online at <https://aerobasegroup.com/nsn/5945-01-226-2900>

Thread Class:

2a single mounting facility

Overall Length:

1.281 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.425 inches single mounting facility

Overall Height:

1.109 inches

Overall Width:

0.859 inches

Case Material:

Plastic

Environmental Protection:

Dust tight and shock resistant and vibration resistant

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.285 inches single mounting facility

Contact Material:

Silver

Contact Surface Treatment:

Gold flash

End Application:

6525-01-159-3009 field radiographic/fluoroscopic x-ray system; model dxd 350 ii

Frequency In Hertz:

60.0

Purpose For Which Designed:

General

Coil Quantity:

1

Winding Dc Resistance Rating:

650.0 ohms all windings

Duty Type:

Continuous

Mounting Facility Type And Quantity:

1 threaded stud single mounting facility

Pile-up Main Contact Form Arrangement:

4c

Cubic Measure:

1.517 cubic inches

Thread Size:

0.099 inches single mounting facility

Minimum Differential Electrical Operating Rating:

0.9 watts

Main Contact Load Current Rating At Maximum Rated Voltage:

5.0 amperes ac resistive load

Main Contact Maximum Voltage Rating In Volts:

240.0 ac

Energizing Element Power Rating:

2.0 volts-amperes

Precious Material And Location:

Contacts gold and contacts silver

Precious Material:

Gold and silver

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

14 tab, solder lug all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A03300