NSN 5945-01-226-4611

Reed Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-226-4611
Overall Length:
1.100 inches
Overall Height:
Between 0.590 inches and 0.610 inches
Overall Width:
1.062 inches
Case Material:
Metal
Environmental Protection:
Hermetic and shock resistant and vibration resistant
Winding Quantity:
1
Coil Quantity:
1
Winding Dc Resistance Rating:
250.0 ohms single winding
Duty Type:
Continuous
Mounting Facility Type And Quantity:
1 plug-in terminal single mounting facility
Features Provided:
Coil voltage suppression
Nonpile-up Main Contact Arrangement:
2 pole, double throw, one position momentary
Operating Voltage Rating And Type At Specificationified Temp:
12.0 volts dc 25 degrees celsius single winding
Main Contact Load Current Rating At Maximum Rated Voltage:
75.0 milliamperes ac resistive load and 75.0 milliamperes dc resistive load
Main Contact Maximum Voltage Rating In Volts:
98.0 ac and 98.0 dc
Special Features:
One terminal grounded to case
Test Data Document:
81349-mil-r-83407 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
9 pin all functions
Specification Data:
81349-mil-r-83407/3 government specification
Shelf Life:
N/a

--

Unit Of Measure:

NSN 5945-01-226-4611

Reed Relay - Page 2 of 2



Demilitarization:

No

Fiig:

A03300