# NSN 5945-01-226-9960

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-226-9960

## **Overall Length:**

1.280 inches

#### Center To Center Distance Between Mounting Facilities Parallel To Width:

0.500 inches single mounting facility

#### **Overall Height:**

0.860 inches

#### **Overall Width:**

0.810 inches

#### **Mounting Slot Width:**

0.133 inches single mounting facility

#### **Case Material:**

Metal

**Environmental Protection:** 

Hermetic

#### Fragility Factor:

Moderately rugged

## End Application:

Mini vast

#### Winding Quantity:

1

#### **Purpose For Which Designed:**

General

#### **Coil Quantity:**

1

## Winding Dc Resistance Rating:

100.0 ohms single winding

## Duty Type:

Continuous

## Arc Quenching Method:

Air

## Mounting Facility Type And Quantity:

3 slotted hole single mounting facility

## Storage Type:

General purpose warehouse

## Features Provided:

Polarized

## Cubic Measure:

1.037 cubic inches

## Mounting Facility Pattern:

Triangle single mounting facility

## Nonpile-up Main Contact Arrangement:

4 pole, double throw, one position momentary

# NSN 5945-01-226-9960

Electromagnetic Relay - Page 2 of 2



#### Time Delay:

0.006 seconds fixed operate and release time Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle: 1.062 inches single mounting facility and 1.078 inches single mounting facility **Operating Voltage Rating And Type At Specificationified Temp:** 12.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 5.0 amperes ac resistive load Main Contact Maximum Voltage Rating In Volts: 200.0 ac **Terminal Type And Quantity:** 14 wire hook all functions Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A03300