# NSN 5945-01-227-6444

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-227-6444

## Overall Length:

2.688 inches

## Center To Center Distance Between Mounting Facilities Parallel To Length:

2.375 inches single mounting facility

## Center To Center Distance Between Mounting Facilities Parallel To Width:

0.625 inches single mounting facility

#### **Overall Height:**

4.125 inches

**Overall Width:** 

2.469 inches

#### Mounting Slot Width:

0.250 inches single mounting facility

Fragility Factor:

Moderately rugged

#### End Application:

Othbanfps118

#### Winding Quantity:

1

## **Purpose For Which Designed:**

General

## **Coil Quantity:**

1

## Winding Dc Resistance Rating:

122.0 ohms single winding

## Duty Type:

Continuous

## Arc Quenching Method:

Air

## Mounting Facility Type And Quantity:

2 slotted hole single mounting facility

#### Storage Type:

General purpose warehouse

#### **Cubic Measure:**

27.376 cubic inches

#### **Mounting Facility Pattern:**

Diagonal single mounting facility

## Nonpile-up Main Contact Arrangement:

7 pole, single throw, normally open, momentary action

## **Operating Current Rating And Type:**

200.0 milliamperes dc single winding

#### Time Delay:

0.022 seconds fixed operate time

## NSN 5945-01-227-6444

Electromagnetic Relay - Page 2 of 2



Operating Voltage Rating And Type At Specificationified Temp:

24.0 volts dc 25 degrees celsius single winding

## Main Contact Load Current Rating At Maximum Rated Voltage:

15.0 amperes ac resistive load

Main Contact Maximum Voltage Rating In Volts:

300.0 ac

Terminal Type And Quantity:

16 screw all functions

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A03300