# NSN 5945-01-227-6446

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-227-6446

## **Overall Length:**

1.968 inches

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

1.712 inches single mounting facility

### **Overall Height:**

1.301 inches

#### **Overall Width:**

1.268 inches

#### Mounting Slot Width:

0.177 inches single mounting facility

#### **Case Material:**

Plastic

**Environmental Protection:** 

#### Dustproof

Fragility Factor:

## Moderately rugged

**Contact Material:** 

Silver

End Application:

6130-01-177-0794

#### Winding Quantity:

1

#### **Purpose For Which Designed:**

General

#### **Coil Quantity:**

1

### Winding Dc Resistance Rating:

108.0 ohms single winding and 132.0 ohms single winding

#### **Duty Type:**

Continuous

#### Arc Quenching Method:

Air

## Mounting Facility Type And Quantity:

2 slotted hole single mounting facility

## Storage Type:

General purpose warehouse

## Cubic Measure:

3.663 cubic inches

## Mounting Facility Pattern:

In-line single mounting facility

## Nonpile-up Main Contact Arrangement:

1 pole, single throw, normally open, momentary action

# NSN 5945-01-227-6446

Electromagnetic Relay - Page 2 of 2



Time Delay:

0.015 seconds fixed operate time

**Operating Voltage Rating And Type At Specificationified Temp:** 

12.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

30.0 amperes ac resistive load and 30.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

250.0 ac and 150.0 dc

**Energizing Element Power Rating:** 

3.0 watts

**Precious Material And Location:** 

Contacts silver

**Precious Material:** 

Silver

Terminal Type And Quantity:

4 tab, solder lug all functions

Shelf Life:

N/a

---

Unit Of Measure:

Demilitarization:

No

Fiig:

A03300