# NSN 5945-01-227-6448

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-227-6448

| Overall Length:   |  |  |
|---|--|--|
| 1.718 inches  |  |  |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |  |  |
| 1.446 inches single mounting facility                                     |  |  |
| Center To Center Distance Between Mounting Facilities Parallel To Width:  |  |  |
| 0.625 inches single mounting facility                                     |  |  |
| Overall Height:   |  |  |
| 1.025 inches  |  |  |
| Overall Width:  |  |  |
| 1.635 inches  |  |  |
| Mounting Slot Width:  |  |  |
| 0.150 inches single mounting facility                                     |  |  |
| Case Material:  |  |  |
| Metal   |  |  |
| Environmental Protection:   |  |  |
| Hermetic  |  |  |
| Fragility Factor:   |  |  |
| Moderately rugged   |  |  |
| End Application:  |  |  |
| B-1b 10b76c   |  |  |
| Frequency In Hertz:   |  |  |
| 400.0   |  |  |
| Winding Quantity:   |  |  |
| 1   |  |  |
| Purpose For Which Designed:   |  |  |
| General   |  |  |
| Coil Quantity:  |  |  |
| 1   |  |  |
| Duty Type:  |  |  |
| Continuous  |  |  |
| Arc Quenching Method:   |  |  |
| Air   |  |  |
| Mounting Facility Type And Quantity:                                      |  |  |
| 4 slotted hole single mounting facility                                   |  |  |
| Storage Type:   |  |  |
| General purpose warehouse   |  |  |
| Cubic Measure:  |  |  |
| 2.879 cubic inches  |  |  |

**Nonpile-up Main Contact Arrangement:** 

Rectangular single mounting facility

**Mounting Facility Pattern:** 

3 pole, double throw, one position momentary

## NSN 5945-01-227-6448

Electromagnetic Relay - Page 2 of 2



| Time | Del | ay: |
|------|-----|-----|
|------|-----|-----|

0.05 seconds fixed release time

**Operating Voltage Rating And Type At Specificationified Temp:** 

115.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

15.0 amperes ac inductive load and 12.0 amperes dc inductive load

**Main Contact Maximum Voltage Rating In Volts:** 

115.0 ac and 28.0 dc

#### **Test Data Document:**

81349-mil-r-6106 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Terminal Type And Quantity:**

11 wire hook all functions

### **Specification Data:**

96906-ms27743 government standard

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A03300

Mil-std (military Standard):

Mil-r-6106 spec.