NSN 5945-01-227-6450

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-227-6450

Overall Length:
0.810 inches
Overall Height:
0.617 inches
Overall Width:
0.410 inches
Case Material:
Metal
Environmental Protection:
Dustproof
Fragility Factor:
Moderately rugged
Winding Quantity:
1
Purpose For Which Designed:
Specific
Coil Quantity:
1
Winding Dc Resistance Rating:
310.0 ohms single winding
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
1 terminal single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
0.205 cubic inches
Nonpile-up Main Contact Arrangement:
2 pole, double throw, one position momentary
Criticality Code Justification:
Feat
Time Delay:
0.006 seconds fixed operate time
Operating Voltage Rating And Type At Specificationified Temp:
12.0 volts dc 25 degrees celsius single winding
Main Contact Load Current Rating At Maximum Rated Voltage:
100.0 milliamperes dc lamp load
Main Contact Maximum Voltage Rating In Volts:
115 0 ac and 29 0 dc

115.0 ac and 28.0 dc

NSN 5945-01-227-6450

Electromagnetic Relay - Page 2 of 2



Special Features:

Failure rate level 1.0 percent per 10000 operations

Test Data Document:

81349-mil-r-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

8 pin all functions

Specification Data:

81349-mil-r-39016/44 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300