NSN 5945-01-228-1760

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-228-1760

Overall Length:
2.190 inches
Overall Diameter:
1.130 inches
Case Material:
Metal
Environmental Protection:
Dustproof
Unthreaded Mounting Hole Diameter:
0.141 inches single mounting facility
Fragility Factor:
Moderately rugged
End Application:
Othbanfps118
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Winding Dc Resistance Rating:
290.0 ohms single winding
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
3 unthreaded hole single mounting facility
Storage Type:
General purpose warehouse
Mounting Facility Pattern:
Ciruclar single mounting facility
Nonpile-up Main Contact Arrangement:
1 pole, single throw, normally closed, momentary action
Time Delay:
0.015 seconds fixed operate and release time
Operating Voltage Rating And Type At Specificationified Temp:
26.5 volts dc 25 degrees celsius single winding
Main Contact Load Current Rating At Maximum Rated Voltage:
12.0 amperes dc resistive load
Main Contact Maximum Voltage Rating In Volts:
10000.0 dc

NSN 5945-01-228-1760

Electromagnetic Relay - Page 2 of 2



Test Data Document:

81349-mil-r-83725 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

4 tab, solder lug all functions

Specification Data:

81349-mil-r-83725/10 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300