## NSN 5945-01-228-5511

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-228-5511

Thread Class:
2a single mounting facility
Thread Direction:
Right-hand single mounting facility
Overall Length:
1.374 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.350 inches single mounting facility
Overall Height:
1.358 inches
Overall Width:
0.734 inches
Case Material:
Plastic
Environmental Protection:
Dustproof
Fragility Factor:
Moderately rugged
Contact Material:
Silver
Contact Surface Treatment:
Gold
End Application:
F/tf-15a acft
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Winding Dc Resistance Rating:
430.0 ohms single winding
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
2 threaded stud single mounting facility
Storage Type:
General purpose warehouse

Cubic Measure: 1.369 cubic inches

## NSN 5945-01-228-5511

Electromagnetic Relay - Page 2 of 2



Thready Qty Per Inch (tpi):
48 single mounting facility
Thread Size:
0.099 inches single mounting facility
Mounting Facility Pattern:
In-line single mounting facility
Nonpile-up Main Contact Arrangement:
6 pole, double throw, one position momentary
Operating Voltage Rating And Type At Specificationified Temp
24.0 volts dc 25 degrees celsius single winding
Main Contact Load Current Rating At Maximum Rated Voltage:
5.0 amperes ac resistive load and 5.0 amperes dc resistive load
Main Contact Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Energizing Element Power Rating:
1.5 watts
Precious Material And Location:
Contacts silver and contact surfaces gold
Precious Material:
Silver and gold
Thread Series Designator:
Unc single mounting facility
Terminal Type And Quantity:
20 tab, solder lug all functions
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A03300