NSN 5945-01-229-6834

Reed Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-229-6834

Overall Length:
1.100 inches
Overall Height:
Between 0.590 inches and 0.610 inches
Overall Width:
0.515 inches
Case Material:
Metal
Environmental Protection:
Hermetic and shock resistant and vibration resistant
Winding Quantity:
1
Coil Quantity:
1
Winding Dc Resistance Rating:
500.0 ohms single winding
Duty Type:
Continuous
Mounting Facility Type And Quantity:
1 plug-in terminal single mounting facility
Features Provided:
Coil voltage suppression
Nonpile-up Main Contact Arrangement:
1 pole, single throw, normally open, momentary action
Operating Voltage Rating And Type At Specificationified Temp:
12.0 volts dc 25 degrees celsius single winding
Main Contact Load Current Rating At Maximum Rated Voltage:
50.0 milliamperes ac resistive load and 50.0 milliamperes dc resistive load
Main Contact Maximum Voltage Rating In Volts:
375.0 ac and 375.0 dc
Test Data Document:
81349-mil-r-83407 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
4 pin all functions
Specification Data:
81349-mil-r-83407/3 government specification
Shelf Life:
N/a
Unit Of Measure:

No

Demilitarization:

NSN 5945-01-229-6834

Reed Relay - Page 2 of 2



Fiig:

A03300