

View Online at <https://aerobasegroup.com/nsn/5945-01-230-2169>

Overall Length:

1.718 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.625 inches single mounting facility

Overall Height:

1.320 inches

Overall Width:

1.025 inches

Mounting Slot Width:

0.150 inches single mounting facility

Case Material:

Metal

Environmental Protection:

Hermetic

Fragility Factor:

Moderately rugged

End Application:

Control syste

Winding Quantity:

1

Purpose For Which Designed:

General

Coil Quantity:

1

Winding Dc Resistance Rating:

290.0 ohms single winding

Duty Type:

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

3 slotted hole single mounting facility

Storage Type:

General purpose warehouse

Cubic Measure:

2.324 cubic inches

Mounting Facility Pattern:

Triangle single mounting facility

Nonpile-up Main Contact Arrangement:

4 pole, double throw, one position momentary

Criticality Code Justification:

Feat

Time Delay:

0.015 seconds fixed operate and release time

Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:

1.446 inches single mounting facility

Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes ac lamp load and 2.0 amperes dc lamp load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Special Features:

Failure rate level 0.3 percent

Terminal Type And Quantity:

14 pin all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A03300

Mil-std (military Standard):

Mil-r-6106 spec.