NSN 5945-01-230-2173

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-230-2173

Overall Length:
2.875 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.375 inches single mounting facility
Overall Height:
7.500 inches
Overall Width:
1.031 inches
Case Material:
Metal
Environmental Protection:
Dustproof
Unthreaded Mounting Hole Diameter:
0.199 inches single mounting facility
Fragility Factor:
Moderately rugged
Contact Material:
Silver
Contact Surface Treatment:
Gold
End Application:
An/tsq-120
Winding Quantity:
2
Purpose For Which Designed:
General
Coil Quantity:
2
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
2 unthreaded hole single mounting facility
Storage Type:
General purpose warehouse
Features Provided:
Latching contacts
Cubic Measure:
22.230 cubic inches
Mounting Facility Pattern:

In-line single mounting facility

NSN 5945-01-230-2173

Electromagnetic Relay - Page 2 of 2



Nonpile-up Main Contact Arrangement:

48 pole, double throw, one position momentary

Time Delay:

0.03 seconds fixed operate and release time

Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius all windings

Main Contact Load Current Rating At Maximum Rated Voltage:

5.0 amperes ac resistive load and 5.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

120.0 ac and 28.0 dc

Precious Material And Location:

Contacts silver and contact surfaces gold

Precious Material:

Silver and gold

Terminal Type And Quantity:

148 tab, solder lug all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A03300