## NSN 5945-01-230-9213

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-230-9213

## **Overall Length:**

2.500 inches

### **Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.990 inches single mounting facility and 2.010 inches single mounting facility

### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.052 inches single mounting facility and 1.072 inches single mounting facility

#### **Overall Height:**

Between 2.350 inches and 2.470 inches

#### **Overall Width:**

1.465 inches

#### **Environmental Protection:**

Hermetic

#### **Unthreaded Mounting Hole Diameter:**

0.173 inches single mounting facility

#### **Fragility Factor:**

Moderately rugged

## **Winding Quantity:**

•

## **Purpose For Which Designed:**

General

## **Coil Quantity:**

.

#### Winding Dc Resistance Rating:

2.6 kilohms single winding

## **Duty Type:**

Continuous

### **Arc Quenching Method:**

Air

#### **Mounting Facility Type And Quantity:**

4 unthreaded hole single mounting facility

## Storage Type:

General purpose warehouse

## **Cubic Measure:**

8.826 cubic inches

### **Mounting Facility Pattern:**

Rectangular single mounting facility

## **Nonpile-up Main Contact Arrangement:**

3 pole, single throw, normally open, momentary action

## Time Delay:

0.025 seconds fixed operate time

## Operating Voltage Rating And Type At Specificationified Temp:

115.0 volts dc 25 degrees celsius single winding

# NSN 5945-01-230-9213

Electromagnetic Relay - Page 2 of 2



## Main Contact Load Current Rating At Maximum Rated Voltage:

20.0 amperes ac motor load and 20.0 amperes dc motor load

**Main Contact Maximum Voltage Rating In Volts:** 

200.0 ac and 28.0 dc

**Terminal Type And Quantity:** 

8 screw all functions

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A03300