# NSN 5945-01-230-9217

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-230-9217

#### **Overall Length:**

4.235 inches

## Center To Center Distance Between Mounting Facilities Parallel To Length:

3.687 inches single mounting facility

## Center To Center Distance Between Mounting Facilities Parallel To Width:

3.500 inches single mounting facility

#### **Overall Height:**

4.531 inches

**Overall Width:** 

4.220 inches

**Case Material:** 

Metal

**Environmental Protection:** 

Dustproof

**Unthreaded Mounting Hole Diameter:** 

0.233 inches single mounting facility

#### **Fragility Factor:**

Moderately rugged

Winding Quantity:

1

**Purpose For Which Designed:** 

General

**Coil Quantity:** 

1

Winding Dc Resistance Rating:

1.23 kilohms single winding

**Duty Type:** 

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

Storage Type:

General purpose warehouse

Cubic Measure:

80.976 cubic inches

**Mounting Facility Pattern:** 

Rectangular single mounting facility

## Nonpile-up Main Contact Arrangement:

3 pole, single throw, normally open, momentary action

Time Delay:

0.03 seconds fixed operate time

NSN 5945-01-230-9217

Electromagnetic Relay - Page 2 of 2



#### Operating Voltage Rating And Type At Specificationified Temp:

115.0 volts dc 25 degrees celsius single winding

#### Main Contact Load Current Rating At Maximum Rated Voltage:

100.0 amperes ac resistive load and 100.0 amperes dc resistive load

#### Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

## Terminal Type And Quantity:

8 screw all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300