# NSN 5945-01-230-9664

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-230-9664

Overall Length:

0.370 inches

**Overall Height:** 

0.398 inches

**Overall Width:** 

0.370 inches

Case Material:

Metal

Environmental Protection:

Hermetic

Fragility Factor:

Moderately rugged

End Application:

Alm and 226 hts f

Winding Quantity:

1

Purpose For Which Designed:

Specific

**Coil Quantity:** 

1

Winding Dc Resistance Rating:

1.56 kilohms single winding

Duty Type:

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

1 terminal single mounting facility

#### Storage Type:

General purpose warehouse

#### Cubic Measure:

0.054 cubic inches

## Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

## Criticality Code Justification:

Feat

#### Time Delay:

0.002 seconds fixed operate time

Operating Voltage Rating And Type At Specificationified Temp:

26.5 volts dc 25 degrees celsius single winding

## Main Contact Load Current Rating At Maximum Rated Voltage:

100.0 milliamperes dc lamp load

## NSN 5945-01-230-9664

Electromagnetic Relay - Page 2 of 2



#### Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

#### **Special Features:**

Failure rate level 0.1 percent per 10000 cycles

#### **Test Data Document:**

81349-mil-r-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### Terminal Type And Quantity:

8 wire lead all functions

#### **Specification Data:**

81349-mil-r-39016/9 government specification

Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

#### Fiig:

A03300