# NSN 5945-01-232-2786

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-232-2786

## **Overall Length:**

1.062 inches

## Center To Center Distance Between Mounting Facilities Parallel To Length:

0.850 inches single mounting facility

# Center To Center Distance Between Mounting Facilities Parallel To Width:

0.300 inches single mounting facility

#### **Overall Height:**

0.470 inches

#### **Overall Width:**

0.610 inches

#### **Case Material:**

Metal

**Environmental Protection:** 

Hermetic

#### **Unthreaded Mounting Hole Diameter:**

0.096 inches single mounting facility

#### **Fragility Factor:**

Moderately rugged

# End Application:

Impss phy sec

## Winding Quantity:

2

## Purpose For Which Designed:

General

### **Coil Quantity:**

2

### Winding Dc Resistance Rating:

975.0 ohms all windings

### Duty Type:

Continuous

### Arc Quenching Method:

Air

# Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

### Storage Type:

General purpose warehouse

### **Features Provided:**

Polarized and latching contacts

## **Cubic Measure:**

0.304 cubic inches

### **Mounting Facility Pattern:**

Rectangular single mounting facility

# NSN 5945-01-232-2786

Electromagnetic Relay - Page 2 of 2



**Nonpile-up Main Contact Arrangement:** 4 pole, double throw, one position momentary **Criticality Code Justification:** Feat **Time Delay:** 0.004 seconds fixed operate and release time **Operating Voltage Rating And Type At Specificationified Temp:** 26.5 volts dc 25 degrees celsius all windings Main Contact Load Current Rating At Maximum Rated Voltage: 125.0 milliamperes ac resistive load and 2.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc **Special Features:** Failure rate level 1.0 percent **Test Data Document:** 81349-mil-r-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 16 wire hook all functions **Specification Data:** 81349-mil-r-39016/36 government specification Shelf Life: Unit Of Measure: **Demilitarization:** Fiig: A03300

N/a

No