NSN 5945-01-232-2787

Electromagnetic Relay - Page 1 of 2

Overall Length: 1.718 inches

Time Delay:

0.01 seconds fixed operate and release time



View Online at https://aerobasegroup.com/nsn/5945-01-232-2787

Center To Center Distance Between Mounting Facilities Parallel To Length:
1.446 inches single mounting facility
Overall Height:
1.300 inches
Overall Width:
0.515 inches
Mounting Slot Width:
0.150 inches single mounting facility
Case Material:
Metal
Environmental Protection:
Hermetic
Fragility Factor:
Moderately rugged
End Application:
Hoses x fitti
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Winding Dc Resistance Rating:
80.0 ohms single winding
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
2 slotted hole single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
1.150 cubic inches
Mounting Facility Pattern:
In-line single mounting facility
Nonpile-up Main Contact Arrangement:
2 pole, double throw, one position momentary

NSN 5945-01-232-2787

Electromagnetic Relay - Page 2 of 2



Operating Voltage Rating And Type At Specificationified Temp:

12.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes ac lamp load and 2.0 amperes dc lamp load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Terminal Type And Quantity:

8 pin all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300

Mil-std (military Standard):

Mil-r-6106 spec.