NSN 5945-01-232-2788

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-232-2788

Overall Length:			
6.125 inches			
Center To Center Distance Between Mounting Facilities Parallel To Length:			
3.750 inches single mounting facility			
Center To Center Distance Between Mounting Facilities Parallel To Width:			
2.500 inches single mounting facility			
Overall Height:			
4.750 inches			
Overall Width:			
2.875 inches			
Case Material:			
Metal			
Environmental Protection:			
Dustproof			
Unthreaded Mounting Hole Diameter:			
0.219 inches single mounting facility			
Fragility Factor:			
Moderately rugged			
End Application:			
Dead reckonin			
Frequency In Hertz:			
60.0			
Winding Quantity:			
1			
Purpose For Which Designed:			
General			
Coil Quantity:			
1			
Duty Type:			
Continuous			
Arc Quenching Method:			
Air			
Mounting Facility Type And Quantity:			
4 unthreaded hole single mounting facility			
Storage Type:			
General purpose warehouse			
Cubic Measure:			
83.644 cubic inches			
Mounting Facility Pattern:			
Rectangular single mounting facility			
Nonpile-up Main Contact Arrangement:			
1 pole, single throw, normally open, momentary action and 1 pole, single throw, normally closed, momentary action			

NSN 5945-01-232-2788

Electromagnetic Relay - Page 2 of 2



	Time	De	lay:
--	------	----	------

0.002 seconds fixed operate and release time

Operating Voltage Rating And Type At Specificationified Temp:

440.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

10.0 amperes ac resistive load

Main Contact Maximum Voltage Rating In Volts:

440.0 ac

Terminal Type And Quantity:

6 screw all functions

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A03300