# NSN 5945-01-233-1149

Reed Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-233-1149

## **Overall Length:**

0.770 inches

### **Overall Height:**

0.375 inches

## **Overall Width:**

Between 0.290 inches and 0.310 inches

#### **Case Material:**

Plastic

#### **Environmental Protection:**

Salt spray resistant and shock resistant and vibration resistant

#### Winding Quantity:

1

### Coil Quantity:

1

#### Winding Dc Resistance Rating:

125.0 ohms single winding

Duty Type:

Continuous

## Mounting Facility Type And Quantity:

1 printed circuit terminal single mounting facility

## Features Provided:

Coil voltage suppression

#### Nonpile-up Main Contact Arrangement:

2 pole, single throw, normally open, momentary action

#### **Operating Voltage Rating And Type At Specificationified Temp:**

5.0 volts dc 25 degrees celsius single winding

#### Main Contact Load Current Rating At Maximum Rated Voltage:

500.0 milliamperes dc resistive load

#### Main Contact Maximum Voltage Rating In Volts:

100.0 dc

#### **Test Data Document:**

81349-mil-r-83516 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### Terminal Type And Quantity:

6 pin all functions

#### **Specification Data:**

81349-mil-r-83516/1 government specification

#### Shelf Life:

N/a

#### Unit Of Measure:

---

## Demilitarization:

No

# NSN 5945-01-233-1149

Reed Relay - Page 2 of 2

**Fiig:** A03300

