NSN 5945-01-234-3036

Electromagnetic Relay - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5945-01-234-3036 | | | | | | |
|---------------------------------------------------------------------------|--|--|--|--|--|--|
| Overall Length: | | | | | | |
| 2.890 inches | | | | | | |
| Center To Center Distance Between Mounting Facilities Parallel To Length: | | | | | | |
| 1.972 inches single mounting facility | | | | | | |
| Center To Center Distance Between Mounting Facilities Parallel To Width: | | | | | | |
| 1.380 inches single mounting facility | | | | | | |
| Overall Height: | | | | | | |
| 2.640 inches | | | | | | |
| Overall Width: | | | | | | |
| 1.730 inches | | | | | | |
| Case Material: | | | | | | |
| Metal | | | | | | |
| Environmental Protection: | | | | | | |
| Dustproof | | | | | | |
| Unthreaded Mounting Hole Diameter: | | | | | | |
| 0.157 inches single mounting facility | | | | | | |
| Fragility Factor: | | | | | | |
| Moderately rugged | | | | | | |
| Winding Quantity: | | | | | | |
| 1 | | | | | | |
| Purpose For Which Designed: | | | | | | |
| General | | | | | | |
| Coil Quantity: | | | | | | |
| 1 | | | | | | |
| Duty Type: | | | | | | |
| Continuous | | | | | | |
| Arc Quenching Method: | | | | | | |
| Air | | | | | | |
| Mounting Facility Type And Quantity: | | | | | | |
| 4 unthreaded hole single mounting facility | | | | | | |
| Storage Type: | | | | | | |
| General purpose warehouse | | | | | | |
| Cubic Measure: | | | | | | |
| 13.199 cubic inches | | | | | | |
| Mounting Facility Pattern: | | | | | | |
| Rectangular single mounting facility | | | | | | |
| Nonpile-up Main Contact Arrangement: | | | | | | |
| 3 pole, single throw, normally open, momentary action | | | | | | |
| Operating Voltage Rating And Type At Specificationified Temp: | | | | | | |

24.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

20.0 amperes ac resistive load

NSN 5945-01-234-3036

Electromagnetic Relay - Page 2 of 2



| Main | Contact | Maximum | Voltage | Rating | ln | Volts: |
|------|---------|---------|---------|--------|----|--------|
| | | | | | | |

230.0 ac

Terminal Type And Quantity:

8 screw all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300