NSN 5945-01-235-1200

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-235-1200

view Online at https://defobasegroup.com/nsi//3343-01-233-1200
Thread Class:
2a single mounting facility
Thread Direction:
Right-hand single mounting facility
Overall Length:
2.940 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
2.375 inches single mounting facility
Center To Center Distance Between Mounting Facilities Parallel To Width:
2.156 inches single mounting facility
Overall Height:
3.450 inches
Overall Width:
2.560 inches
Case Material:
Metal
Environmental Protection:
Dustproof
Fragility Factor:
Moderately rugged
End Application:
4920-01-179-8469
Frequency In Hertz:
50.0
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
4 threaded stud single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
12.814 cubic inches
Thready Qty Per Inch (tpi):

32 single mounting facility

NSN 5945-01-235-1200

Electromagnetic Relay - Page 2 of 2



т	h	re	a	d	S	iz	6	

0.138 inches single mounting facility

Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

3 pole, double throw, one position momentary

Time Delay:

10.00 seconds fixed operate and release time

Operating Voltage Rating And Type At Specificationified Temp:

115.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes ac resistive load and 10.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

11 wire hook all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300