# NSN 5945-01-235-1201

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-235-1201

Thread Class:				
2a single mounting facility				
Thread Direction:				
Right-hand single mounting facility				
Overall Length:				
2.940 inches				
Center To Center Distance Between Mounting Facilities Parallel To Length:				
2.375 inches single mounting facility				
Center To Center Distance Between Mounting Facilities Parallel To Width:				
2.156 inches single mounting facility				
Overall Height:				
3.670 inches				
Overall Width:				
2.560 inches				
Case Material:				
Metal				
Environmental Protection:				
Dustproof				
Fragility Factor:				
Moderately rugged				
End Application:				
4920-01-179-8469				
Frequency In Hertz:				
60.0				
Winding Quantity:				
1				
Purpose For Which Designed:				
General				
Coil Quantity:				
1				
Duty Type:				
Continuous				
Arc Quenching Method:				
Air				
Mounting Facility Type And Quantity:				
4 threaded stud single mounting facility				
Storage Type:				
General purpose warehouse				
Cubic Measure:				
27.621 cubic inches				
Thready Qty Per Inch (tpi):				

32 single mounting facility

# NSN 5945-01-235-1201

Electromagnetic Relay - Page 2 of 2



Th	reac	I Si	ze:

0.138 inches single mounting facility

# **Mounting Facility Pattern:**

Rectangular single mounting facility

# **Nonpile-up Main Contact Arrangement:**

3 pole, double throw, one position momentary

## Time Delay:

10.00 seconds fixed operate and release time

# **Operating Voltage Rating And Type At Specificationified Temp:**

115.0 volts ac 25 degrees celsius single winding

#### Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes ac resistive load and 10.0 amperes dc resistive load

## **Main Contact Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

## **Thread Series Designator:**

Unc single mounting facility

## **Terminal Type And Quantity:**

11 wire hook all functions

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A03300