NSN 5945-01-235-4066

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-235-4066

Overall Length:
4.750 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
3.937 inches single mounting facility
Center To Center Distance Between Mounting Facilities Parallel To Width:
3.937 inches single mounting facility
Overall Height:
5.360 inches
Overall Width:
4.750 inches
Case Material:
Metal
Unthreaded Mounting Hole Diameter:
0.218 inches single mounting facility
Fragility Factor:
Moderately rugged
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
4 unthreaded hole single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
120.935 cubic inches
Mounting Facility Pattern:
Rectangular single mounting facility
Nonpile-up Main Contact Arrangement:
3 pole, single throw, normally open, double make, momentary action
Time Delay:
0.10 seconds fixed operate and release time
Nonpile-up Auxiliary Contact Arrangement:

115.0 ac and 28.0 dc

2 pole, double throw, one position momentary

Auxiliary Contact Maximum Voltage Rating In Volts:

NSN 5945-01-235-4066

Electromagnetic Relay - Page 2 of 2



Operating Voltage Rating And Type At Specificationified Temp:

115.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

100.0 amperes ac resistive load

Main Contact Maximum Voltage Rating In Volts:

480.0 ac

Auxiliary Contact Load Current Rating At Maximum Rated Voltage:

5.0 amperes ac resistive load and 5.0 amperes dc resistive load

Terminal Type And Quantity:

14 threaded stud all functions

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

Yes - demil/mli

Fiig:

A03300