NSN 5945-01-235-4093

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-235-4093

Overall Length.
Overall Length:
1.500 inches
Overall Height:
2.656 inches
Overall Width:
1.375 inches
Case Material:
Plastic
Environmental Protection:
Dustproof
Fragility Factor:
Moderately rugged
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
1 plug-in terminal single mounting facility
Storage Type:
General purpose warehouse
General purpose warehouse Cubic Measure:
Cubic Measure:
Cubic Measure: 5.478 cubic inches
Cubic Measure: 5.478 cubic inches Nonpile-up Main Contact Arrangement:
Cubic Measure: 5.478 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, single throw, normally open, momentary action and 2 pole, single throw, normally closed, momentary action
Cubic Measure: 5.478 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, single throw, normally open, momentary action and 2 pole, single throw, normally closed, momentary action Time Delay:
Cubic Measure: 5.478 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, single throw, normally open, momentary action and 2 pole, single throw, normally closed, momentary action Time Delay: 3.00 seconds adjustable operate time and 30.00 seconds adjustable operate time
Cubic Measure: 5.478 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, single throw, normally open, momentary action and 2 pole, single throw, normally closed, momentary action Time Delay: 3.00 seconds adjustable operate time and 30.00 seconds adjustable operate time Operating Voltage Rating And Type At Specificationified Temp:
Cubic Measure: 5.478 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, single throw, normally open, momentary action and 2 pole, single throw, normally closed, momentary action Time Delay: 3.00 seconds adjustable operate time and 30.00 seconds adjustable operate time Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts dc 25 degrees celsius single winding
Cubic Measure: 5.478 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, single throw, normally open, momentary action and 2 pole, single throw, normally closed, momentary action Time Delay: 3.00 seconds adjustable operate time and 30.00 seconds adjustable operate time Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage:
Cubic Measure: 5.478 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, single throw, normally open, momentary action and 2 pole, single throw, normally closed, momentary action Time Delay: 3.00 seconds adjustable operate time and 30.00 seconds adjustable operate time Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 10.0 amperes ac resistive load and 10.0 amperes dc resistive load
Cubic Measure: 5.478 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, single throw, normally open, momentary action and 2 pole, single throw, normally closed, momentary action Time Delay: 3.00 seconds adjustable operate time and 30.00 seconds adjustable operate time Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 10.0 amperes ac resistive load and 10.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts:
Cubic Measure: 5.478 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, single throw, normally open, momentary action and 2 pole, single throw, normally closed, momentary action Time Delay: 3.00 seconds adjustable operate time and 30.00 seconds adjustable operate time Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 10.0 amperes ac resistive load and 10.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 120.0 ac and 28.0 dc

N/a

NSN 5945-01-235-4093

Electromagnetic Relay - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A03300