NSN 5945-01-236-1061

Electromagnetic Relay - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5945-01-236-1061 |
|---|
| Overall Length: |
| 3.531 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 0.875 inches single mounting facility and 1.750 inches single mounting facility |
| Overall Height: |
| 3.750 inches |
| Overall Width: |
| 2.438 inches |
| Mounting Slot Width: |
| 0.203 inches single mounting facility |
| Case Material: |
| Plastic |
| Environmental Protection: |
| Dustproof |
| Center To Center Distance Between Mounting Facilities Parallel To Height: |
| 3.250 inches single mounting facility |
| Fragility Factor: |
| Moderately rugged |
| Contact Material: |
| Silver |
| Contact Surface Treatment: |
| Cadmium plated |
| End Application: |
| 4920-01-083-2644 |
| Frequency In Hertz: |
| Between 50.0 and 60.0 |
| Winding Quantity: |
| 1 |
| Purpose For Which Designed: |
| General |
| Coil Quantity: |
| 1 |
| Winding Dc Resistance Rating: |
| 5.0 ohms single winding |
| Duty Type: |
| Continuous |
| Arc Quenching Method: |
| Air |
| Mounting Facility Type And Quantity: |
| 6 slotted hole single mounting facility |

Storage Type:

General purpose warehouse

NSN 5945-01-236-1061

Electromagnetic Relay - Page 2 of 2



| Cubic Measure: |
|---|
| 32.282 cubic inches |
| Mounting Facility Pattern: |
| Rectangular single mounting facility |
| Nonpile-up Main Contact Arrangement: |
| 4 pole, single throw, normally open, momentary action |
| Operating Voltage Rating And Type At Specificationified Temp: |
| 24.0 volts ac 25 degrees celsius single winding |
| Main Contact Load Current Rating At Maximum Rated Voltage: |
| 50.0 amperes ac resistive load |
| Main Contact Maximum Voltage Rating In Volts: |
| 600.0 ac |
| Special Features: |
| Horizontal mounting |
| Precious Material And Location: |
| Contacts silver |
| Precious Material: |
| Silver |
| Terminal Type And Quantity: |
| 10 screw all functions |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |

Fiig: A03300