## NSN 5945-01-237-5149

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-237-5149

Main Contact Load Current Rating At Maximum Rated Voltage: 3.0 amperes ac resistive load and 3.0 amperes dc resistive load

Overall Length:
2.250 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.750 inches single mounting facility
Overall Height:
2.250 inches
Overall Width:
1.750 inches
Case Material:
Metal
Environmental Protection:
Hermetic
Unthreaded Mounting Hole Diameter:
0.171 inches single mounting facility
Fragility Factor:
Moderately rugged
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
2 unthreaded hole single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
8.859 cubic inches
Mounting Facility Pattern:
In-line single mounting facility
Nonpile-up Main Contact Arrangement:
2 pole, single throw, normally open, momentary action and 2 pole, single throw, normally closed, momentary action
Time Delay:
0.02 seconds fixed operate time
Operating Voltage Rating And Type At Specificationified Temp:
120.0 volts ac 25 degrees celsius single winding

## NSN 5945-01-237-5149

Electromagnetic Relay - Page 2 of 2



440.0 ac and 120.0 dc

**Terminal Type And Quantity:** 

10 screw all functions

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A03300