NSN 5945-01-237-5272

Electromagnetic Relay - Page 1 of 2

Overall Length: 3.000 inches



View Online at https://aerobasegroup.com/nsn/5945-01-237-5272

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.625 inches second mounting facility
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.250 inches second mounting facility
Overall Height:
2.300 inches
Overall Width:
2.700 inches
Case Material:
Metal
Environmental Protection:
Hermetic
Unthreaded Mounting Hole Diameter:
0.012 inches second mounting facility
Fragility Factor:
Moderately rugged
End Application:
Alcc relay
Frequency In Hertz:
60.0
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
6 unthreaded hole second mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
18.630 cubic inches
Mounting Facility Pattern:
Rectangular second mounting facility
Nonpile-up Main Contact Arrangement:

4 pole, double throw, one position momentary

NSN 5945-01-237-5272

Electromagnetic Relay - Page 2 of 2



Time I	Delay:
--------	--------

0.095 seconds fixed operate time

Operating Voltage Rating And Type At Specificationified Temp:

115.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes ac lamp load and 3.0 amperes dc lamp load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Test Data Document:

81349-mil-r-6106 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

14 screw all functions

Specification Data:

96906-ms24568 government standard

Shelf Life:

N/a

Unit Of Measure:

_

Demilitarization:

No

Fiig:

A03300

Mil-std (military Standard):

Mil-r-6106 spec.