# NSN 5945-01-237-5274

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-237-5274

## Thread Class:

2a single mounting facility

## **Thread Direction:**

Right-hand single mounting facility

### **Overall Length:**

1.531 inches

### **Overall Height:**

1.968 inches

### **Overall Width:**

1.406 inches

### **Case Material:**

Plastic

### **Environmental Protection:**

Dustproof

## Fragility Factor:

## Moderately rugged

**Contact Material:** 

Silver

## End Application:

Rawin an/gmd

## Winding Quantity:

1

## Purpose For Which Designed:

General

## **Coil Quantity:**

1

## Winding Dc Resistance Rating:

1.7 kilohms single winding

## Duty Type:

Continuous

### Arc Quenching Method:

Air

# Mounting Facility Type And Quantity:

1 threaded stud single mounting facility

# Storage Type:

General purpose warehouse

# Cubic Measure:

4.236 cubic inches

# Thready Qty Per Inch (tpi):

32 single mounting facility

# Thread Size:

0.138 inches single mounting facility

# NSN 5945-01-237-5274

Electromagnetic Relay - Page 2 of 2



Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary **Time Delay:** 0.015 seconds fixed operate time **Operating Voltage Rating And Type At Specificationified Temp:** 120.0 volts ac 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 15.0 amperes ac resistive load and 15.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 240.0 ac and 28.0 dc **Precious Material And Location:** Contacts silver **Precious Material:** Silver **Thread Series Designator:** Unc single mounting facility **Terminal Type And Quantity:** 8 tab, solder lug all functions Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A03300