

View Online at <https://aerobasegroup.com/nsn/5945-01-237-7303>

Overall Length:

1.280 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.062 inches single mounting facility and 1.078 inches single mounting facility

Overall Height:

0.410 inches

Overall Width:

0.860 inches

Mounting Slot Width:

0.150 inches single mounting facility

Case Material:

Metal

Environmental Protection:

Hermetic

Fragility Factor:

Moderately rugged

Winding Quantity:

2

Purpose For Which Designed:

General

Coil Quantity:

2

Winding Dc Resistance Rating:

730.0 ohms all windings

Duty Type:

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

2 slotted hole single mounting facility

Storage Type:

General purpose warehouse

Features Provided:

Polarized and latching contacts

Cubic Measure:

0.451 cubic inches

Mounting Facility Pattern:

In-line single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Operating Current Rating And Type:

44.0 milliamperes dc all windings

Time Delay:

0.004 seconds fixed operate and release time

Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius all windings

Main Contact Load Current Rating At Maximum Rated Voltage:

1.0 amperes ac lamp load and 1.0 amperes dc lamp load

Main Contact Maximum Voltage Rating In Volts:

200.0 ac and 28.0 dc

Test Data Document:

81349-mil-r-6106 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

10 wire hook all functions

Specification Data:

81349-mil-r-6106/38 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300