NSN 5945-01-238-4629

Electromagnetic Relay - Page 1 of 2

Overall Length: 3.810 inches



View Online at https://aerobasegroup.com/nsn/5945-01-238-4629

Center To Center Distance Between Mounting Facilities Parallel To Length:
2.812 inches single mounting facility
Center To Center Distance Between Mounting Facilities Parallel To Width:
2.812 inches single mounting facility
Overall Height:
4.520 inches
Overall Width:
3.810 inches
Case Material:
Metal
Environmental Protection:
Dustproof
Unthreaded Mounting Hole Diameter:
0.156 inches single mounting facility
Fragility Factor:
Moderately rugged
End Application:
Box, junction
Frequency In Hertz:
60.0
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
4 unthreaded hole single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
65.612 cubic inches
Mounting Facility Pattern:
Rectangular single mounting facility
Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

NSN 5945-01-238-4629

Electromagnetic Relay - Page 2 of 2



	Time	De	lay:
--	------	----	------

1.50 seconds adjustable operate time and 15.00 seconds adjustable operate time

Operating Voltage Rating And Type At Specificationified Temp:

120.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

10.0 amperes ac resistive load and 15.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

240.0 ac and 30.0 dc

Terminal Type And Quantity:

8 screw all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300