NSN 5945-01-238-6707

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-238-6707

Overall Length:

Between 1.735 inches and 1.765 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.346 inches single mounting facility and 1.366 inches single mounting facility

Overall Height:

Between 0.505 inches and 0.535 inches

Overall Width:

Between 0.999 inches and 1.010 inches

Mounting Slot Width:

0.139 inches single mounting facility and 0.149 inches single mounting facility

Case Material:

Metal

Environmental Protection:

Hermetic

Fragility Factor:

Moderately rugged

End Application:

An/bps14to15e

Winding Quantity:

Purpose For Which Designed:

General

Coil Quantity:

Winding Dc Resistance Rating:

7.6 kilohms single winding

Duty Type:

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

2 slotted hole single mounting facility

Storage Type:

General purpose warehouse

Cubic Measure:

0.954 cubic inches

Mounting Facility Pattern:

In-line single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Time Delay:

0.017 seconds fixed operate time

NSN 5945-01-238-6707

Electromagnetic Relay - Page 2 of 2



Operating Voltage Rating	And Type At Specificationified Te	emp:
---------------------------------	-----------------------------------	------

120.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

10.0 amperes ac resistive load

Main Contact Maximum Voltage Rating In Volts:

300.0 ac

Terminal Type And Quantity:

8 pin all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300