NSN 5945-01-239-2049

Reed Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-239-2049

Overall Length: 0.783 inches Overall Height: 0.375 inches Overall Width: 0.383 inches Case Material: Metal Fragility Factor: Moderately rugged Winding Quantity: 1 Purpose For Which Designed: General Coil Quantity: 1 Winding Dc Resistance Rating: 200.0 ohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 1 plug-in terminal single mounting facility Storage Type: General purpose warehouse Features Provided: Coil voltage suppression Cubic Measure: 0.112 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, single throw, normally open, momentary action Operating Voltage Rating And Type At Specificationified Temp: 5.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 500.0 milliamperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 200.0 dc Terminal Type And Quantity:
Overall Height: 0.375 inches Overall Width: 0.383 inches Case Material: Metal Fragility Factor: Moderately rugged Winding Quantity: 1 Purpose For Which Designed: General Coil Quantity: 1 Winding Dc Resistance Rating: 200.0 ohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 1 plug-in terminal single mounting facility Storage Type: General purpose warehouse Features Provided: Coil voltage suppression Cubic Measure: 0.112 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, single throw, normally open, momentary action Operating Voltage Rating And Type At Specificationified Temp: 5.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 500.0 milliamperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 200.0 dc
Overall Width: 0.383 inches Case Material: Metal Fragility Factor: Moderately rugged Winding Quantity: 1 Purpose For Which Designed: General Coil Quantity: 1 Winding Dc Resistance Rating: 200.0 ohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 1 plug-in terminal single mounting facility Storage Type: General purpose warehouse Features Provided: Coil voltage suppression Cubic Measure: 0.112 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, single throw, normally open, momentary action Operating Voltage Rating And Type At Specificationified Temp: 5.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 500.0 milliamperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 200.0 dc
Overall Width: 0.383 inches Case Material: Metal Fragility Factor: Moderately rugged Winding Quantity: 1 Purpose For Which Designed: General Coil Quantity: 1 Winding Dc Resistance Rating: 200.0 ohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 1 plug-in terminal single mounting facility Storage Type: General purpose warehouse Features Provided: Coil voltage suppression Cubic Measure: 0.112 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, single throw, normally open, momentary action Operating Voltage Rating And Type At Specificationified Temp: 5.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 500.0 milliamperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 200.0 dc
O.383 inches Case Material: Metal Fragility Factor: Moderately rugged Winding Quantity: 1 Purpose For Which Designed: General Coil Quantity: 1 Winding Dc Resistance Rating: 200.0 ohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 1 plug-in terminal single mounting facility Storage Type: General purpose warehouse Features Provided: Coil voltage suppression Cubic Measure: 0.112 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, single throw, normally open, momentary action Operating Voltage Rating And Type At Specificationified Temp: 5.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 500.0 milliamperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 200.0 dc
Case Material: Metal Fragility Factor: Moderately rugged Winding Quantity: 1 Purpose For Which Designed: General Coil Quantity: 1 Winding Dc Resistance Rating: 200.0 ohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 1 plug-in terminal single mounting facility Storage Type: General purpose warehouse Features Provided: Coil voltage suppression Cubic Measure: 0.112 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, single throw, normally open, momentary action Operating Voltage Rating And Type At Specificationified Temp: 5.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 500.0 milliamperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 200.0 dc
Metal Fragility Factor: Moderately rugged Winding Quantity: 1 Purpose For Which Designed: General Coil Quantity: 1 Winding Dc Resistance Rating: 200.0 ohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 1 plug-in terminal single mounting facility Storage Type: General purpose warehouse Features Provided: Coil voltage suppression Cubic Measure: 0.112 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, single throw, normally open, momentary action Operating Voltage Rating And Type At Specificationified Temp: 5.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 500.0 milliamperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 200.0 dc
Fragility Factor: Moderately rugged Winding Quantity: 1 Purpose For Which Designed: General Coil Quantity: 1 Winding Dc Resistance Rating: 200.0 ohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 1 plug-in terminal single mounting facility Storage Type: General purpose warehouse Features Provided: Coil voltage suppression Cubic Measure: 0.112 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, single throw, normally open, momentary action Operating Voltage Rating And Type At Specificationified Temp: 5.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 500.0 milliamperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 200.0 dc
Moderately rugged Winding Quantity: 1 Purpose For Which Designed: General Coil Quantity: 1 Winding Dc Resistance Rating: 200.0 ohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 1 plug-in terminal single mounting facility Storage Type: General purpose warehouse Features Provided: Coil voltage suppression Cubic Measure: 0.112 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, single throw, normally open, momentary action Operating Voltage Rating And Type At Specificationified Temp: 5.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 500.0 milliamperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 200.0 dc
Winding Quantity: 1 Purpose For Which Designed: General Coil Quantity: 1 Winding Dc Resistance Rating: 200.0 ohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 1 plug-in terminal single mounting facility Storage Type: General purpose warehouse Features Provided: Coil voltage suppression Cubic Measure: 0.112 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, single throw, normally open, momentary action Operating Voltage Rating And Type At Specificationified Temp: 5.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 500.0 milliamperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 200.0 dc
Purpose For Which Designed: General Coil Quantity: 1 Winding Dc Resistance Rating: 200.0 ohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 1 plug-in terminal single mounting facility Storage Type: General purpose warehouse Features Provided: Coil voltage suppression Cubic Measure: 0.112 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, single throw, normally open, momentary action Operating Voltage Rating And Type At Specificationified Temp: 5.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 500.0 milliamperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 200.0 dc
Purpose For Which Designed: General Coil Quantity: 1 Winding Dc Resistance Rating: 200.0 ohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 1 plug-in terminal single mounting facility Storage Type: General purpose warehouse Features Provided: Coil voltage suppression Cubic Measure: 0.112 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, single throw, normally open, momentary action Operating Voltage Rating And Type At Specificationified Temp: 5.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 500.0 milliamperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 200.0 dc
Coil Quantity: 1 Winding Dc Resistance Rating: 200.0 ohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 1 plug-in terminal single mounting facility Storage Type: General purpose warehouse Features Provided: Coil voltage suppression Cubic Measure: 0.112 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, single throw, normally open, momentary action Operating Voltage Rating And Type At Specificationified Temp: 5.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 500.0 milliamperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 200.0 dc
Coil Quantity: 1 Winding Dc Resistance Rating: 200.0 ohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 1 plug-in terminal single mounting facility Storage Type: General purpose warehouse Features Provided: Coil voltage suppression Cubic Measure: 0.112 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, single throw, normally open, momentary action Operating Voltage Rating And Type At Specificationified Temp: 5.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 500.0 milliamperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 200.0 dc
Winding Dc Resistance Rating: 200.0 ohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 1 plug-in terminal single mounting facility Storage Type: General purpose warehouse Features Provided: Coil voltage suppression Cubic Measure: 0.112 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, single throw, normally open, momentary action Operating Voltage Rating And Type At Specificationified Temp: 5.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 500.0 milliamperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 200.0 dc
Winding Dc Resistance Rating: 200.0 ohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 1 plug-in terminal single mounting facility Storage Type: General purpose warehouse Features Provided: Coil voltage suppression Cubic Measure: 0.112 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, single throw, normally open, momentary action Operating Voltage Rating And Type At Specificationified Temp: 5.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 500.0 milliamperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 200.0 dc
Duty Type: Continuous Mounting Facility Type And Quantity: 1 plug-in terminal single mounting facility Storage Type: General purpose warehouse Features Provided: Coil voltage suppression Cubic Measure: 0.112 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, single throw, normally open, momentary action Operating Voltage Rating And Type At Specificationified Temp: 5.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 500.0 milliamperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 200.0 dc
Duty Type: Continuous Mounting Facility Type And Quantity: 1 plug-in terminal single mounting facility Storage Type: General purpose warehouse Features Provided: Coil voltage suppression Cubic Measure: 0.112 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, single throw, normally open, momentary action Operating Voltage Rating And Type At Specificationified Temp: 5.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 500.0 milliamperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 200.0 dc
Mounting Facility Type And Quantity: 1 plug-in terminal single mounting facility Storage Type: General purpose warehouse Features Provided: Coil voltage suppression Cubic Measure: 0.112 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, single throw, normally open, momentary action Operating Voltage Rating And Type At Specificationified Temp: 5.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 500.0 milliamperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 200.0 dc
Mounting Facility Type And Quantity: 1 plug-in terminal single mounting facility Storage Type: General purpose warehouse Features Provided: Coil voltage suppression Cubic Measure: 0.112 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, single throw, normally open, momentary action Operating Voltage Rating And Type At Specificationified Temp: 5.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 500.0 milliamperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 200.0 dc
1 plug-in terminal single mounting facility Storage Type: General purpose warehouse Features Provided: Coil voltage suppression Cubic Measure: 0.112 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, single throw, normally open, momentary action Operating Voltage Rating And Type At Specificationified Temp: 5.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 500.0 milliamperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 200.0 dc
Storage Type: General purpose warehouse Features Provided: Coil voltage suppression Cubic Measure: 0.112 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, single throw, normally open, momentary action Operating Voltage Rating And Type At Specificationified Temp: 5.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 500.0 milliamperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 200.0 dc
General purpose warehouse Features Provided: Coil voltage suppression Cubic Measure: 0.112 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, single throw, normally open, momentary action Operating Voltage Rating And Type At Specificationified Temp: 5.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 500.0 milliamperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 200.0 dc
Features Provided: Coil voltage suppression Cubic Measure: 0.112 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, single throw, normally open, momentary action Operating Voltage Rating And Type At Specificationified Temp: 5.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 500.0 milliamperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 200.0 dc
Cubic Measure: 0.112 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, single throw, normally open, momentary action Operating Voltage Rating And Type At Specificationified Temp: 5.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 500.0 milliamperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 200.0 dc
Cubic Measure: 0.112 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, single throw, normally open, momentary action Operating Voltage Rating And Type At Specificationified Temp: 5.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 500.0 milliamperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 200.0 dc
 0.112 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, single throw, normally open, momentary action Operating Voltage Rating And Type At Specificationified Temp: 5.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 500.0 milliamperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 200.0 dc
Nonpile-up Main Contact Arrangement: 2 pole, single throw, normally open, momentary action Operating Voltage Rating And Type At Specificationified Temp: 5.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 500.0 milliamperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 200.0 dc
2 pole, single throw, normally open, momentary action Operating Voltage Rating And Type At Specificationified Temp: 5.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 500.0 milliamperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 200.0 dc
Operating Voltage Rating And Type At Specificationified Temp: 5.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 500.0 milliamperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 200.0 dc
5.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 500.0 milliamperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 200.0 dc
Main Contact Load Current Rating At Maximum Rated Voltage: 500.0 milliamperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 200.0 dc
500.0 milliamperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 200.0 dc
Main Contact Maximum Voltage Rating In Volts: 200.0 dc
200.0 dc
Terminal Type And Quantity:
71
6 pin all functions
Shelf Life:
N/a

--

NSN 5945-01-239-2049

Reed Relay - Page 2 of 2



Demilitarization:

No

Fiig:

A03300