## NSN 5945-01-240-2975

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-240-2975

Main Contact Load Current Rating At Maximum Rated Voltage: 5.0 amperes ac resistive load and 5.0 amperes dc resistive load

Overall Length:
4.875 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
4.000 inches single mounting facility
Center To Center Distance Between Mounting Facilities Parallel To Width:
3.875 inches single mounting facility
Overall Height:
3.000 inches
Overall Width:
4.625 inches
Case Material:
Metal
Environmental Protection:
Dustproof
Unthreaded Mounting Hole Diameter:
0.171 inches single mounting facility
Fragility Factor:
Moderately rugged
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
4 unthreaded hole single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
67.640 cubic inches
Mounting Facility Pattern:
Rectangular single mounting facility
Nonpile-up Main Contact Arrangement:
1 pole, single throw, normally open, momentary action and 1 pole, single throw, normally closed, momentary action
Operating Voltage Rating And Type At Specificationified Temp:
120.0 volts ac 25 degrees celsius single winding

## NSN 5945-01-240-2975

Electromagnetic Relay - Page 2 of 2



Main Contact Maximum Voltage Rating In Volts:	Main	Contact	Maximum	Voltage	Rating	In	Volts:
---	------	---------	---------	---------	--------	----	--------

120.0 ac and 28.0 dc

**Terminal Type And Quantity:** 

6 screw all functions

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A03300