# NSN 5945-01-240-3012

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-240-3012

# **Overall Length:**

1.400 inches

### Center To Center Distance Between Mounting Facilities Parallel To Length:

1.200 inches single mounting facility

## **Overall Height:**

0.680 inches

### **Overall Width:**

1.000 inches

#### **Case Material:**

Metal

#### **Environmental Protection:**

Hermetic

#### **Unthreaded Mounting Hole Diameter:**

0.150 inches single mounting facility

#### **Fragility Factor:**

## Moderately rugged

End Application:

## Mc-6 compress

Winding Quantity:

1

**Purpose For Which Designed:** 

General

#### **Coil Quantity:**

1

# Winding Dc Resistance Rating:

16.0 ohms single winding

## Duty Type:

Continuous

# Arc Quenching Method:

Air

# Mounting Facility Type And Quantity:

2 unthreaded hole single mounting facility

## Storage Type:

General purpose warehouse

## Cubic Measure:

0.952 cubic inches

# Mounting Facility Pattern:

In-line single mounting facility

# Nonpile-up Main Contact Arrangement:

1 pole, double throw, one position momentary

# Operating Voltage Rating And Type At Specificationified Temp:

12.0 volts dc 25 degrees celsius single winding

# NSN 5945-01-240-3012

Electromagnetic Relay - Page 2 of 2



## Main Contact Load Current Rating At Maximum Rated Voltage:

100.0 milliamperes ac resistive load

#### Main Contact Maximum Voltage Rating In Volts:

115.0 ac

## Terminal Type And Quantity:

5 threaded stud all functions

Shelf Life:

N/a

Unit Of Measure:

---

## Demilitarization:

No

#### Fiig:

A03300