NSN 5945-01-240-3868

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-240-3868

Overall Length:	
0.610 inches	
Overall Height:	
0.527 inches	
Overall Width:	
0.310 inches	
Case Material:	
Metal	
Environmental Protection:	
Hermetic	
Fragility Factor:	
Moderately rugged	
Winding Quantity:	
1	
Purpose For Which Designed:	
Specific	
Coil Quantity:	
1	
Winding Dc Resistance Rating:	
650.0 ohms single winding	
Duty Type:	
Continuous	
Arc Quenching Method:	
Air	
Mounting Facility Type And Quantity:	
1 terminal single mounting facility	
Storage Type:	
General purpose warehouse	
Cubic Measure:	
0.100 cubic inches	
Nonpile-up Main Contact Arrangement:	
2 pole, double throw, one position momentary	
Criticality Code Justification:	
Feat	
Time Delay:	
0.004 seconds fixed operate and release time	
Operating Voltage Rating And Type At Specificationified Temp:	
18.0 volts dc 25 degrees celsius single winding	
Main Contact Load Current Rating At Maximum Rated Voltage:	
125.0 milliamperes ac resistive load and 2.0 amperes dc resistive load	
Main Contact Maximum Voltage Rating In Volts:	

115.0 ac and 28.0 dc

NSN 5945-01-240-3868

Electromagnetic Relay - Page 2 of 2



Special	Features:
---------	-----------

Failure rate level 0.1 percent

Test Data Document:

81349-mil-r-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

8 pin all functions

Specification Data:

81349-mil-r-39016/13 government specification

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A03300