# NSN 5945-01-240-3871

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-240-3871

**Overall Length:** 

0.810 inches

**Overall Height:** 

0.600 inches

**Overall Width:** 

0.410 inches

**Case Material:** 

Metal

**Environmental Protection:** 

Hermetic

Fragility Factor:

Moderately rugged

Winding Quantity:

1

Purpose For Which Designed:

General

Coil Quantity:

1

Winding Dc Resistance Rating:

40.0 ohms single winding

**Duty Type:** 

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

1 terminal single mounting facility

Storage Type:

General purpose warehouse

**Features Provided:** 

Polarized

Cubic Measure:

0.199 cubic inches

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

**Criticality Code Justification:** 

Feat

Time Delay:

0.004 seconds fixed operate and release time

Operating Voltage Rating And Type At Specificationified Temp:

6.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

160.0 milliamperes dc lamp load

NSN 5945-01-240-3871

Electromagnetic Relay - Page 2 of 2



# Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

## **Special Features:**

Failure rate level 0.1 percent

# **Test Data Document:**

81349-mil-r-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Terminal Type And Quantity:

8 wire hook all functions

### **Specification Data:**

81349-mil-r-39016/6 government specification

Shelf Life:

N/a

### Unit Of Measure:

---

# Demilitarization:

No

# Fiig:

A03300