NSN 5945-01-241-7750

Electromagnetic Relay - Page 1 of 2

Thread Class:

2b single mounting facility



View Online at https://aerobasegroup.com/nsn/5945-01-241-7750

Thread Direction:
Right-hand single mounting facility
Overall Length:
0.950 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.375 inches single mounting facility
Overall Height:
1.407 inches
Overall Width:
0.735 inches
Case Material:
Plastic
Environmental Protection:
Dustproof
Fragility Factor:
Moderately rugged
Contact Material:
Gold and platinum and silver
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Winding Dc Resistance Rating:
700.0 ohms single winding
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
2 threaded hole single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
0.982 cubic inches
Thready Qty Per Inch (tpi):
48 single mounting facility
Thread Size:

Till Cad Oizo.

0.099 inches single mounting facility

NSN 5945-01-241-7750

Electromagnetic Relay - Page 2 of 2



Mounting Facility Pattern:

In-line single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Operating Voltage Rating And Type At Specificationified Temp:

24.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

250.0 milliamperes ac resistive load and 250.0 milliamperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Precious Material And Location:

Contacts gold and contacts platinum and contacts silver

Precious Material:

Gold and platinum and silver

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

8 tab, solder lug all functions

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A03300