NSN 5945-01-242-7010

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-242-7010

view Offinite at https://aerobasegroup.com/hsh/5545-01-242-7010
Overall Length:
2.900 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
2.500 inches single mounting facility
Overall Height:
1.400 inches
Overall Width:
1.525 inches
Mounting Slot Width:
0.150 inches single mounting facility
Case Material:
Plastic
Environmental Protection:
Dustproof
Fragility Factor:
Moderately rugged
Contact Material:
Silver
End Application:
Rs test sys
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Winding Dc Resistance Rating:
32.0 ohms single winding
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
2 slotted hole single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
6.192 cubic inches

Mounting Facility Pattern:
In-line single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, single throw, normally open, momentary action

NSN 5945-01-242-7010

Electromagnetic Relay - Page 2 of 2



Time Delay:
0.02 seconds fixed operate time
Operating Voltage Rating And Type At Specificationified Temp:
6.0 volts dc 25 degrees celsius single winding
Main Contact Load Current Rating At Maximum Rated Voltage:
20.0 amperes ac resistive load and 20.0 amperes dc resistive load
Main Contact Maximum Voltage Rating In Volts:
277.0 ac and 28.0 dc
Energizing Element Power Rating:
1.9 watts
Precious Material And Location:
Contacts silver
Precious Material:
Silver
Terminal Type And Quantity:
6 quick disconnect, male all functions
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A03300