NSN 5945-01-242-7015

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-242-7015 **Overall Length:** 0.375 inches **Overall Diameter:** 0.370 inches **Case Material:** Metal **Environmental Protection:** Hermetic **Fragility Factor:** Moderately rugged **End Application:** Sparrow an/dp **Winding Quantity: Purpose For Which Designed:** General **Coil Quantity:** Winding Dc Resistance Rating: 3.3 kilohms single winding **Duty Type:** Continuous **Arc Quenching Method:** Air **Mounting Facility Type And Quantity:** 1 terminal single mounting facility Storage Type: General purpose warehouse **Features Provided:** Polarized and coil voltage suppression **Cubic Measure:** 0.040 cubic inches **Nonpile-up Main Contact Arrangement:** 2 pole, double throw, one position momentary Time Delay: 0.004 seconds fixed operate time Operating Voltage Rating And Type At Specificationified Temp: 26.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 500.0 milliamperes dc resistive load Main Contact Maximum Voltage Rating In Volts:

28.0 dc

NSN 5945-01-242-7015

Electromagnetic Relay - Page 2 of 2



Terminal Type A	and Quantity	/ :
-----------------	--------------	------------

8 wire lead all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300