## NSN 5945-01-242-9389

Electromagnetic Relay - Page 1 of 2

**Overall Length:** 



View Online at https://aerobasegroup.com/nsn/5945-01-242-9389

1.330 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.062 inches single mounting facility
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.281 inches single mounting facility
Overall Height:
0.460 inches
Overall Width:
1.080 inches
Case Material:
Metal
Environmental Protection:
Hermetic
Unthreaded Mounting Hole Diameter:
0.120 inches single mounting facility
Fragility Factor:
Moderately rugged
End Application:
Gen cont unit
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Winding Dc Resistance Rating:
30.0 ohms single winding
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
4 unthreaded hole single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
0.661 cubic inches
Mounting Facility Pattern:
Rectangular single mounting facility
Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

## NSN 5945-01-242-9389

Electromagnetic Relay - Page 2 of 2



	Time	De	lay:
--	------	----	------

0.005 seconds fixed operate time

**Operating Voltage Rating And Type At Specificationified Temp:** 

6.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

1.0 amperes ac resistive load and 2.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

**Terminal Type And Quantity:** 

8 wire hook all functions

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

**Demilitarization:** 

No

Fiig:

A03300